

Technical Data

Typical measurement speed

Tire rotation frequency	1 rps – 2 rps
Measurement frequency	2 kHz – 4 kHz

Example of a typical sidewall sensor

Measurement range

Measurement width (radial)	80 mm
Measurement height (axial)	50 mm
Measurement distance (axial)	50 mm

Measurement resolution

Height resolution (axial)	min. 30 µm
Radial resolution	0.6 mm
Tangential resolution	0.5 mm – 1.0 mm

Example of a typical tread sensor

Measurement range

Measurement width (axial)	400 mm
Measurement height (radial)	50 mm
Measurement distance (radial)	300 mm

Measurement resolution

Height resolution (radial)	45 µm
Axial resolution	1.5 mm
Tangential resolution	0.5 mm – 1.0 mm

All technical data including the housing dimensions and the measurement distance can be adapted within a wide range to the customer's specific requirements.

For detailed information,
please see our homepage:



Development Center
X-ray Technology EZRT
a division of Fraunhofer Institute
for Integrated Circuits IIS

Management of the institute
Prof. Albert Heuberger
(executive)
Prof. Bernhard Grill
Prof. Alexander Martin

Am Wolfsmantel 33
91058 Erlangen, Germany
Phone +49 9131 776-0
info@iis.fraunhofer.de
www.iis.fraunhofer.de

Division Director
Dr. Norman Uhlmann

Flugplatzstraße 75
90768 Fürth, Germany
info-ezrt@iis.fraunhofer.de
www.iis.fraunhofer.de/ezrt

Contact
Dr.-Ing. Lars Seifert
Phone +49 911 58061-7232
lars.seifert@iis.fraunhofer.de

 **Fraunhofer**
EZRT

Development Center X-ray Technology
at Fraunhofer Institute for
Integrated Circuits IIS


TireChecker

Quality control system
for finished tires

www.iis.fraunhofer.de/ezrt



TireChecker allows complete geometry measurements at high speed



TireChecker System, Courtesy of Seichter GmbH

System Information


The TireChecker system uses contactless laser sheet-of-light sensors and custom image processing algorithms to measure all relevant geometric features of a tire precisely and quickly, keeping pace with today's production. The system's modular architecture allows flexible adaptation to virtually any geometric measurement task, environmental constraint and budgetary requirement. Anything from a simple system consisting of a single sidewall sensor to a full system covering the tire's entire surface is configurable. Bulge measurement is performed on the entire sidewall regardless of lettering or other surface features. Custom measurement algorithms can also be integrated into the software on request.

Existing laser sensor equipment can be utilized if required; design of customer specific sensors is available as well. Existing machinery can be upgraded with a TireChecker system or it can be designed into new tire testing machines, being customizable to fit different mechanical situations as well as capable of being integrated into a number of PLC architectures.

Motivation

The TireChecker quality control system is a standard solution when reliable inspection and precise measurement of high-quality tires for geometry and bulges is required. With more than 20 years of service, leading tire manufacturers worldwide trust the TireChecker as a proven solution for testing of tires. The system was developed at the Fraunhofer IIS in close cooperation with key tire manufacturers and testing equipment builders.

It is available integrated into turnkey systems or as an upgrade from our licensed partners. It is also available for licensing to offer testing machinery suppliers a cost effective solution for sheet-of-light geometry measurement.



TireChecker user interface showing sidewall and tread data at a glance